

TABLE OF CONTENTS

Single-Spindle Cutters	RC2 – RC5
RC-Series: 3.5-, 4-, 5- and 6-foot	RC2
4- through 7-foot BrushBull™, Standard-Duty	RC3
5- through 7-foot BrushBull, Medium-Duty	RC4
5- through 7-foot BrushBull, Heavy-Duty	RC5
Ditch Bank Cutter	RC6
5- and 6-foot Hydraulic Drive	RC6
Dual-Spindle Cutters	RC7 – RC12
8-foot, 30 Series Dual-Spindle	RC7
10-foot, 40 Series Dual-Spindle	RC8
8-foot, 50 Series Dual-Spindle	RC9
8-foot Offset, 50 Series Dual-Spindle	RC10
10-foot, 50 Series Dual-Spindle	RC11
10-foot Offset, 50 Series Dual-Spindle	RC12
Batwing® Cutters	RC13 – RC29
12-foot Dual-Wing, For Compact/Utility Tractors	RC13
10.5-foot, Standard-Duty Single-Wing	RC14
15-foot, Standard-Duty Dual-Wing	RC15
10.5-foot, Heavy-Duty Single-Wing	RC16 – RC17
15-foot, Heavy-Duty Dual-Wing	RC18 – RC19
10.5-foot, Extreme-Duty Single-Wing	RC20 – RC21
15-foot, Extreme-Duty Dual-Wing	RC22 – RC23
20-foot, Standard-Duty Dual-Wing	RC24
20-foot, Heavy-Duty Dual-Wing	RC25
13.5-foot, Extreme-Duty Single-Wing	RC26 – RC27
20-foot, Extreme-Duty Dual-Wing	RC28 – RC29

NOTE: All gearbox horsepower ratings listed in the following specifications are based on Woods' field testing.

RC-SERIES SINGLE-SPINDLE ROTARY CUTTER

3.5-, 4-, 5- and 6-foot – RC42.20, RC48.20, RC60.20 & RC72.20

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

- | | |
|--|--|
| Tractor PTO hp requirement:
15 – 40 PTO hp (RC42.20 & RC48.20);
20 – 50 PTO hp (RC60.20 & RC72.20) | Thrown Object Protection:
† Rear steel band deflector and front
rubber belt deflector – standard;
Front and rear chain shielding – optional |
| Tractor PTO speed: 540 rpm | Cut: 1-inch diameter |
| Tractor 3-point hitch size:
Cat 1 (quick-hitch ready) | Blade size: 1/2-inch x 3-inch |
| Tail Wheel: 4-inch x 16-inch
laminated tire with 360° rotation | Gearbox hp rating: 50 hp
3-year gearbox warranty |



WARNING: STANDARD FRONT RUBBER AND REAR STEEL BAND DEFLECTOR SHIELD OR OPTIONAL CHAIN SHIELDING must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property.

See “Match Your Tractor” terms and conditions for ordering criteria below.

5% ADDITIONAL DISCOUNT ON FIVE (5) PACKS** AS DEFINED BELOW.

BASE UNIT

Model No.	Width (ft.)	Drive	Woods® Orange Part No.	Green ¹ Part No. **	Orange ² Part No. **	Blue ³ Part No. **	Shipping Wt. (lbs.)	Suggested List Price Per Unit ***	5 Pack List Price Per Unit ***
RC42.20*	3.5	Shear Pin	619543	619543JD	619543KO	619543VB	396	\$ 1,546.00	—
		Slip Clutch	619543C	619543JDC	619543KOC	619543VBC	408	1,729.00	—
RC48.20	4	Shear Pin	619544	619544JD	619544KO	619544VB	432	1,620.00	\$ 1,539.00
		Slip Clutch	619544C	619544JDC	619544KOC	619544VBC	444	1,808.00	1,718.00
RC60.20	5	Shear Pin	619545	619545JD	619545KO	619545VB	494	1,753.00	1,665.00
		Slip Clutch	619545C	619545JDC	619545KOC	619545VBC	506	1,950.00	1,853.00
RC72.20	6	Shear Pin	619546	619546JD	619546KO	619546VB	569	2,086.00	1,982.00
		Slip Clutch	619546C	619546JDC	619546KOC	619546VBC	580	2,272.00	2,158.00

* DISCONTINUED – LIMITED QUANTITIES

** Painted colors to match ¹ Green, ² Orange and ³ Blue tractors.

*** Five (5) packs **MUST** be five (5) of the same size and color model; pricing reflects 5% discount with rounding. Five packs not available on RC42.20 models. **Note:** Add “A” to the end of the part number if not ordering in five (5) pack quantities.

† **NOTE:** All units are shipped with rear metal band and front rubber belt deflector shields. These are NON-RETURNABLE items.

ACCESSORIES

Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
1037925	RC42.20	Front and Rear Chain Shielding	28	\$ 339.00
1037926	RC48.20	Front and Rear Chain Shielding	31	361.00
1037927	RC60.20	Front and Rear Chain Shielding	36	392.00
1037928	RC72.20	Front and Rear Chain Shielding	45	422.00
1023325	All Models	TQH1 Category 1 Quick Hitch	79	364.00
1038335	All Models	Optional Bolt-On Skid Shoes	4	70.00

RC-Series cutters are available in the tractor colors as listed on this page.

“MATCH YOUR TRACTOR” TERMS & CONDITIONS

1. “Match Your Tractor” RC42.20, RC48.20, RC60.20 & RC72.20 models are built to order, requiring lead times that may vary.
2. “Match Your Tractor” orders are non-cancellable. Units and their accessories may not be returned.
3. Changes to existing orders must have the Dealer Service Supervisor’s approval.
4. Repair parts are not available in “Match Your Tractor” (including Woods orange units).
5. Woods reserves the right to limit quantities and to modify or cancel this offering at any time.

Prices and specifications subject to change without notice.
 Prices effective May 17, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BRUSHBULL™ SINGLE-SPINDLE ROTARY CUTTER, STANDARD-DUTY

4-, 5- and 6-foot, 30 Series & 7-foot 40 Series –
BB48.30, BB60.30, BB72.30 & BB84.40

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

Cat 1, 3-point hitch, 540 rpm
(BB48.30, BB60.30, BB72.30 Cat 1;
BB84.40 Cat 1 & 2)

Safety shielded Cat 3 slip-clutch driveline
(BB48.30, BB60.30, BB72.30);
Cat 4 slip clutch driveline (BB84.40)

Driveline holder

ASABE quick-hitch compatible

Greasable "Quick Change" blade pins **EXCLUSIVE FEATURE**

Factory filled gearboxes with
80-90W EP gear lube

Two 3-inch x 3-inch full
length structural tubes

Heavy-duty clevis hitch

Cut: 2 inches diameter

Blade size: 1/2-inch x 4-inch

Gearbox rating:

65 hp (BB48.30 & BB60.30)

75 hp (BB72.30),

90 hp (BB84.40)

6-year limited gearbox warranty



WARNING: SAFETY SHIELDING STANDARD EQUIPMENT. Rubber shielding or chain shielding must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property.

See "Match Your Tractor" terms and conditions for ordering criteria below.

BASE UNIT									
Model No.	Width (ft.)	Laminated Tail Wheel	Front/Rear Shielding	Woods® Orange Part No.	Green ¹ Part No.*	Orange ² Part No.*	Blue ³ Part No.*	Shipping Wt. (lbs.)	Suggested List Price
BB48.30	4	Single	Belt	610114	610114JD	610114KO	610114VB	590	\$ 2,315.00
			Chain	610114W	610114JDW	610114KOW	610114VBW	635	2,600.00
BB60.30	5	Single	Belt	610115	610115JD	610115KO	610115VB	672	2,636.00
			Chain	610115W	610115JDW	610115KOW	610115VBW	728	2,937.00
BB72.30	6	Single	Belt	610116	610116JD	610116KO	610116VB	811	3,188.00
			Chain	610116W	610116JDW	610116KOW	610116VBW	878	3,555.00
BB84.40	7	Single	Belt	610117	610117JD	610117KO	610117VB	1041	4,743.00
			Chain	610117W	610117JDW	610117KOW	610117VBW	1118	5,163.00
BB84.40D	7	Dual	Belt	610117D	610117DJD	610117DKO	610117DVB	1177	5,256.00
			Chain	610117DW	610117DJDW	610117DKOW	610117DVBW	1254	5,676.00

* Painted colors to match ¹ Green, ² Orange and ³ Blue tractors.

ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
10521	All Models	Check Chain: for mowing height adjustment	17	\$ 116.00
1023325	All Models	TQH1 Category 1 Quick Hitch	79	364.00
610225	BB84.40	Dual Tail Wheel with 16" Laminated Tires – Replacement Kit	292	968.00
610139	BB48.30	Front and Rear Belt Shield Replacement Kit	20	147.00
610141	BB60.30	Front and Rear Belt Shield Replacement Kit	24	166.00
610143	BB72.30	Front and Rear Belt Shield Replacement Kit	27	182.00
610145	BB84.40	Front and Rear Belt Shield Replacement Kit	33	196.00
610138	BB48.30	Front and Rear Chain Shield Replacement Kit	65	432.00
610140	BB60.30	Front and Rear Chain Shield Replacement Kit	80	467.00
610142	BB72.30	Front and Rear Chain Shield Replacement Kit	94	549.00
610144	BB84.40	Front and Rear Chain Shield Replacement Kit	110	616.00

BrushBull standard-duty cutters are available in the tractor colors as listed on this page.

"MATCH YOUR TRACTOR" TERMS & CONDITIONS

1. Product availability in most cases will be 30 to 60 days and sometimes less.
2. "Match Your Tractor" BrushBulls are built to order, requiring lead times that may vary.
3. "Match Your Tractor" orders are non-cancellable. Units and their accessories may not be returned.
4. Changes to existing orders must have the Dealer Service Supervisor's approval.
5. Repair parts are only available in black.
6. Woods reserves the right to limit quantities and to modify or cancel this offering at any time.

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BRUSHBULL™ SINGLE-SPINDLE ROTARY CUTTER, MEDIUM-DUTY

5-, 6- and 7-foot, 50 Series – BB60.50, BB72.50 & BB84.50

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

- 3-point hitch, 540 rpm
(BB60.50, BB72.50 Cat 1 & 2;
BB84.50 Cat 2 & 3)
- Safety shielded Cat 4 slip-clutch driveline
- Driveline holder
- ASABE quick-hitch compatible
- Greasable “Quick Change” blade pins **◀ EXCLUSIVE FEATURE**
- Factory filled gearboxes with
80-90W EP gear lube
- Two 3-inch x 3-inch full length structural tubes
- Heavy-duty clevis hitch
- Cut: 3 inches diameter
- Blade size: 1/2-inch x 4-inch
- Gearbox rating: 150 hp
- 6-year limited gearbox warranty



WARNING: SAFETY SHIELDING STANDARD EQUIPMENT. Rubber shielding or chain shielding must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property.

See “Match Your Tractor” terms and conditions for ordering criteria below.

BASE UNIT							
Model No.	Width (ft.)	Laminated Tail Wheel	Front/Rear Shielding	Woods® Orange Part No.	Green Part No.*	Shipping Wt. (lbs.)	Suggested List Price
BB60.50	5	Single	Belt	609855	609855JD	932	\$ 3,796.00
			Chain	609855W	609855JDW	1006	4,249.00
BB72.50	6	Single	Belt	609856	609856JD	1064	4,241.00
			Chain	609856W	609856JDW	1152	4,774.00
BB72.50D	6	Dual	Belt	609856D	609856DJD	1200	4,744.00
			Chain	609856DW	609856DJDW	1288	5,277.00
BB84.50	7	Single	Belt	609857	609857JD	1228	5,708.00
			Chain	609857W	609857JDW	1331	6,324.00
BB84.50D	7	Dual	Belt	609857D	609857DJD	1364	6,221.00
			Chain	609857DW	609857DJDW	1467	6,837.00

* Painted to match Green tractors.

ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
10521	All Models	Check Chain: for mowing height adjustment	17	\$ 116.00
1023325	BB60.50, BB72.50	TQH1 Category 1 Quick Hitch	79	364.00
610225	BB72.50, BB84.50	Dual Tail Wheel with 16” Laminated Tires – Replacement Kit	292	968.00
610124	BB60.50	Round Stump Jumper Kit	24	202.00
603839	BB72.50, BB84.50	Round Stump Jumper Kit	52	348.00
610147	BB60.50	Front and Rear Belt Shield Replacement Kit	30	175.00
610149	BB72.50	Front and Rear Belt Shield Replacement Kit	37	196.00
610151	BB84.50	Front and Rear Belt Shield Replacement Kit	41	207.00
610146	BB60.50	Front and Rear Chain Shield Replacement Kit	104	462.00
610148	BB72.50	Front and Rear Chain Shield Replacement Kit	124	533.00
610150	BB84.50	Front and Rear Chain Shield Replacement Kit	144	616.00

BrushBull standard-duty cutters are available in the tractor colors as listed on this page.

“MATCH YOUR TRACTOR” TERMS & CONDITIONS

1. Product availability in most cases will be 30 to 60 days and sometimes less.
2. “Match Your Tractor” BrushBulls are built to order, requiring lead times that may vary.
3. “Match Your Tractor” orders are non-cancellable. Units and their accessories may not be returned.
4. Changes to existing orders must have the Dealer Service Supervisor’s approval.
5. Repair parts are only available in black.
6. Woods reserves the right to limit quantities and to modify or cancel this offering at any time.

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BRUSHBULL™ SINGLE-SPINDLE ROTARY CUTTER, HEAVY-DUTY

5-, 6- and 7-foot, 60 Series - BB60.60, BB72.60 & BB84.60

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

3-point hitch, 540 rpm
(BB60.60, BB72.60 Cat 1 & 2;
BB84.60 Cat 2 & 3)

Safety shielded Cat 5 slip-clutch driveline

Driveline holder

ASABE quick-hitch compatible

Greasable "Quick Change" blade pins ◀ **EXCLUSIVE FEATURE**

Factory filled gearboxes with
80-90W EP gear lube

Two 3-inch x 3-inch full
length structural tubes

Heavy-duty clevis hitch

Cut: 4 inches diameter

Blade size: 1/2-inch x 4-inch

Gearbox rating: 210 hp

6-year limited gearbox warranty



WARNING: STANDARD CHAIN SHIELDING must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property.

BASE UNIT						
Model No.	Width (ft.)	Laminated Tail Wheel	Front/Rear Shielding	Part No.	Shipping Wt. (lbs.)	Suggested List Price
BB60.60	5	Single	Chain	610135W	1082	\$ 6,059.00
BB72.60D	6	Dual	Chain	610136DW	1366	7,020.00
BB84.60D	7	Dual	Chain	610137DW	1568	9,407.00

ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
10521	All Models	Check Chain: for mowing height adjustment	17	\$ 116.00
1023325	BB60.60, BB72.60	TQH1 Category 1 Quick Hitch	79	364.00
610225	BB72.60, BB84.60	Dual Tail Wheel with 16" Laminated Tires – Replacement Kit	292	968.00
610124	BB60.60	Round Stump Jumper Kit	24	202.00
603839	BB72.60, BB84.60	Round Stump Jumper Kit	52	348.00
610146	BB60.60	Front and Rear Chain Shield Replacement Kit	104	462.00
610148	BB72.60	Front and Rear Chain Shield Replacement Kit	124	533.00
610150	BB84.60	Front and Rear Chain Shield Replacement Kit	144	616.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

DITCH BANK ROTARY CUTTER, HYDRAULIC DRIVE

5- and 6-foot – DBH5.31 & DBH6.31

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

30 Series: Recommended tractor hp = 60 – 150

Sloped top, 10-gauge deck

10-gauge side frame with 9.5-inch depth

40 hp maximum at cutting deck

Easy “Quick Change” blade pins ◀ **EXCLUSIVE FEATURE**

Cut: 2 inches diameter

Horizontal cutting reach: 30 inches maximum

4,000 lb. minimum tractor weight (DBH5.31)

5,000 lb. minimum tractor weight (DBH6.31)

3,000 lb. 3-point hitch minimum lift capacity required

Cat 4 input PTO shaft

Clevis hitch – Cat 2 & 3 (3-Point and Quick Hitch)

35-gallon hydraulic tank capacity

6-year gearbox warranty



DISCONTINUED
LIMITED QUANTITIES

WARNING: SAFETY CHAIN SHIELDING STANDARD EQUIPMENT. Must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property.

All hydraulics and deck assembled and leak tested at factory.

Dealer required preparations:

Dealer supplies counter weights (380 lbs. required, counter balance weight kit [1045138 below] or tractor suitcase style).

Dealer fills oil reservoir (35 gallons).

BASE UNIT

Model No.	Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
DBH5.31	603674	1-3/8", 540 rpm PTO, side-mounted, 5' single spindle for Cat 2 & 3, 3-pt. hitch, chain shielding.	1750	\$ 13,620.00
DBH5.31Q	603674Q	1-3/8", 1000 rpm PTO, side-mounted, 5' single spindle for Cat 2 & 3, 3-pt. hitch, chain shielding.	1750	13,620.00
DBH6.31	603675	1-3/8", 540 rpm PTO, side-mounted, 6' single spindle for Cat 2 & 3, 3-pt. hitch, chain shielding.	2000	15,375.00
DBH6.31Q	603675Q	1-3/8", 1000 rpm PTO, side-mounted, 6' single spindle for Cat 2 & 3, 3-pt. hitch, chain shielding.	2000	15,375.00

ACCESSORIES

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045320	Gage Wheel Assembly: for outside of deck for height control	70	\$ 396.00
1043273	Tail Wheel Assembly: for center frame for 3-point height control	132	817.00
1045138	Counter Balance Weight Kit (minimum weight needed)	385	764.00
1045139	Counter Balance: for additional weight if needed	131	258.00
1041830CRT	Dealer-Installed Oil Cooler: for extreme operating temperatures and conditions	40	1,756.00
10521	Check Chain: for mowing height adjustment	17	116.00

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

8-foot, 30 Series – DS8.30 & MDS8.30

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

- 30 Series:** Recommended tractor hp =
35 – 75 hp (pull-type), 45 – 75 hp (mounted)
- Sloped top, 10-gauge deck
- 7-gauge side frame with 10-inch depth
- Safety shielded Cat 4 slip-clutch driveline
- Pivoting clevis hitch on pull-type
- Easy "Quick Change" blade pins ◀ **EXCLUSIVE FEATURE**
- Cut: 1.5 inches diameter
- Cutting height: 2 – 12 inches
- 100 hp splitter gearbox,
75 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: SAFETY SHIELDING STANDARD EQUIPMENT. Rubber shielding or chain shielding must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**8' Dual-Spindle Cutter, Dealer-Assembled.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR COMPLETE PULL-TYPE; SECTION 1 FOR MOUNTED.**

SECTION 1: BASE UNIT (MUST Choose One)						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DS8.30	96428	Pull-Type	Belt	540 rpm PTO, Cat 4 CV input drive, pivoting clevis tongue, cylinder and hose. Order choice of wheels below.	1367	\$ 8,103.00
DS8.30W	96429		Chain		1420	8,287.00
MDS8.30	96430	3-point Mounted	Belt	540 rpm PTO for Cat 1 & 2, 3-point clevis hitch (quick-hitch ready), Cat 4 input drive, two tail wheel arms and 16" laminated caster wheels.	1185	6,654.00
MDS8.30W	96431		Chain		1238	6,837.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Used On	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	DS8.30	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	DS8.30	21" O.D. Solid Laminated Tire & Rim	70	317.00
1039976	DS8.30	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	DS8.30	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
1040656	All Models	Front Rubber Belting and Rear Band Replacement Kit	36	\$ 249.00
1040713	All Models	Front and Rear Chain Shielding Replacement Kit	89	435.00
1042775	All Models	Bolt-On Skid Shoes	5	63.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

10-foot, 40 Series – DS10.40 & MDS10.40

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

- 40 Series:** Recommended tractor hp =
40 – 120 hp (pull-type), 60 – 120 hp (mounted)
- Sloped top, 10-gauge deck
- 7-gauge side frame with 10-inch depth
- Cat 4 input PTO shaft (DS10.40)
- Cat 5 input PTO shaft (MDS10.40)
- Pivoting clevis hitch on pull-type
- Easy “Quick Change” blade pins ◀ **EXCLUSIVE FEATURE**
- Cut: 2 inches diameter
- 120 hp splitter gearbox,
90 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: SAFETY SHIELDING STANDARD EQUIPMENT. Rubber shielding or chain shielding must be used for all non-agricultural uses and in areas where possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement’s maximum transport speed.

**10' Dual-Spindle Cutter, Dealer-Assembled.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR COMPLETE PULL-TYPE; SECTION 1 FOR MOUNTED.**

SECTION 1: BASE UNIT (MUST Choose One)						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DS10.40	96432	Pull-Type	Belt	540 rpm PTO, Cat 4 CV input drive, pivoting clevis tongue, cylinder and hose. Order choice of wheels below.	1742	\$ 10,309.00
DS10.40W	96433		Chain		1813	10,549.00
MDS10.40	96434	3-point Mounted	Belt	540 rpm PTO for Cat 2 & 3, 3-point clevis hitch (quick-hitch ready), Cat 5 input drive, two tail wheel arms and 16" laminated caster wheels.	1601	9,179.00
MDS10.40W	96435		Chain		1672	9,420.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Used On	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	DS10.40	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	DS10.40	21" O.D. Solid Laminated Tire & Rim	70	317.00
1039976	DS10.40	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	DS10.40	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
1040705	All Models	Front Rubber Belting and Rear Band Replacement Kit	42	\$ 330.00
1040716	All Models	Front and Rear Chain Shielding Replacement Kit	113	570.00
1042775	All Models	Bolt-On Skid Shoes	5	63.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

8-foot, 50 Series – DS8.50 & MDS8.50

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

- 50 Series:** Recommended tractor hp =
40 – 200 hp (pull-type), 55 – 200 hp (mounted)
- Sloped top, 10-gauge deck
- 1/4-inch side frame with 13-inch depth
- Cat 5 input PTO shaft; Cat 6 CV
- Clevis hitch – Cat 2 & 3
(3-Point and Quick Hitch)
- Pivoting clevis hitch on pull-type
- Spring cushion axle
- Variable wheel spacing
- Easy “Quick Change” blade pins ◀ **EXCLUSIVE FEATURE**
- Cut: 3 inches diameter
- 205 hp splitter gearbox,
160 hp spindle gearboxes
- Bolt-on skid shoes included
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement’s maximum transport speed.

**8’ Dual-Spindle Cutter, Dealer-Assembled.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR COMPLETE PULL-TYPE; SECTION 1 FOR MOUNTED.**

SECTION 1: BASE UNIT (MUST Choose One)						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DS8.50W	96437	Pull-Type	Chain	540 rpm PTO, Cat 6 CV input drive, pivoting clevis tongue, cylinder and hose. Order choice of wheels below.	2189	\$ 11,023.00
MDS8.50W	96441	3-point Mounted	Chain	540 rpm PTO for Cat 2 & 3, 3-point clevis hitch (quick-hitch ready), cylinder and hose, Cat 5 input drive, two tail wheel arms and 16” laminated caster wheels.	2164	9,153.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Used On	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	DS8.50	15” Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	DS8.50	21” O.D. Solid Laminated Tire & Rim	70	317.00
1039976	DS8.50	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	DS8.50	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
1042295	All Models	Front and Rear Chain Shielding Replacement Kit	132	\$ 446.00
1017310	DS8.50	Dual Hub Kit (Pull-type units only) – Add 2 Additional Wheels Per Kit	30	290.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

8-foot Offset, 50 Series – DSO8.50

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

50 Series: Recommended tractor hp = 40 – 200 hp

Hydraulic offset:

21 inches right or 5 inches left of center

Sloped top, 10-gauge deck

1/4-inch side frame with 13-inch depth

Cat 5 input PTO shaft

Cat 2 or 3 semi-mount hitch

Spring cushion axle

Variable wheel spacing

Two 21-inch laminated tires

Easy “Quick Change” blade pins ◀ **EXCLUSIVE FEATURE**

Cut: 3 inches diameter

205 hp splitter gearbox,
160 hp spindle gearboxes

Bolt-on skid shoes included

6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement’s maximum transport speed.

8’ Offset Dual-Spindle Cutter, Dealer-Assembled.

SECTION 1: BASE UNIT						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DSO8.50W	96445	Semi-Mounted	Chain	540 rpm PTO, Cat 5 input drive, cylinder and hose.	2441	\$ 11,662.00

SECTION 2: ACCESSORIES (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1042295	Front and Rear Chain Shielding Replacement Kit	132	\$ 446.00

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

10-foot, 50 Series – DS10.50 & MDS10.50

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

50 Series: Recommended tractor hp =
50 – 200 hp (pull-type),
65 – 200 hp (mounted)

Sloped top, 10-gauge deck

1/4-inch side frame with 13-inch depth

Safety shielded Cat 6 CV input driveline:
pull-type units

Safety shielded Cat 5 heavy input driveline:
mounted units

Clevis hitch – Cat 2 & 3 (3-Point and Quick Hitch)

Pivoting clevis hitch on pull-type

Spring cushion axle

Variable wheel spacing

Easy “Quick Change” blade pins **EXCLUSIVE FEATURE**

Cutting width: 120 inches

Transport width: 127 inches

Cutting height: 2 to 12 inches

Cut: 3 inches in diameter

205 hp splitter gearbox,
160 hp blade spindle gearboxes

6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement’s maximum transport speed.

**10’ Dual-Spindle Cutter, Dealer-Assembled.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR COMPLETE PULL-TYPE; SECTION 1 FOR MOUNTED.**

SECTION 1: BASE UNIT (MUST Choose One)						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DS10.50W	96449	Pull-Type	Chain	540 rpm PTO, Cat 6 CV input drive, pivoting clevis tongue, cylinder and hose. Order choice of wheels below.	2483	\$ 13,236.00
MDS10.50W	96453	3-point Mounted	Chain	540 rpm PTO for Cat 2 & 3, 3-point clevis hitch (quick-hitch ready), Cat 5 input drive, two tail wheel arms and 16” laminated caster wheels.	2468	12,645.00
MDS10.50QW	96455	3-point Mounted	Chain	1-3/8” 1000 rpm PTO for Cat 2 & 3, 3-point clevis hitch (quick-hitch ready), Cat 5 input drive, two tail wheel arms and 16” laminated caster wheels.	2389	12,645.00
MDS10.50QW	96463	3-point Mounted	Chain	1-3/4” 1000 rpm PTO for Cat 2 & 3, 3-point clevis hitch (quick-hitch ready), Cat 5 input drive, two tail wheel arms and 16” laminated caster wheels.	2386	12,645.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Used On	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	DS10.50	15” Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	DS10.50	21” O.D. Solid Laminated Tire & Rim	70	317.00
1017030	DS10.50	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	DS10.50	29” O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	DS10.50	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	DS10.50	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: ACCESSORIES (Dealer-Installed)				
Part No.	Used On	Description	Shipping Wt. (lbs.)	Suggested List Price
1042260	All Models	Front and Rear Chain Shielding Replacement Kit	165	\$ 601.00
1017310	DS10.50	Dual Hub Kit (Pull-type units only) – Add 2 Additional Wheels Per Kit	30	290.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

DUAL-SPINDLE ROTARY CUTTER

10-foot Offset, 50 Series – DSO10.50

DEALER ASSEMBLED

FEATURES & SPECIFICATIONS:

50 Series: Recommended tractor hp = 50 – 200 hp

Hydraulic offset:

27 inches right or 5 inches left of center

Sloped top, 10-gauge deck

1/4-inch side frame with 13-inch depth

Safety shielded Cat 5 heavy input driveline

Cat 2 or 3 semi-mount hitch

Spring cushion axle

Variable wheel spacing

Two 21-inch laminated tires

Easy “Quick Change” blade pins ◀ **EXCLUSIVE FEATURE**

Cutting width: 120 inches

Transport width: 127 inches

Cutting height: 2 to 12 inches

Cut: 3 inches in diameter

205 hp splitter gearbox,

160 hp blade spindle gearboxes

6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement’s maximum transport speed.

10’ Offset Dual-Spindle Cutter, Dealer-Assembled.

SECTION 1: BASE UNIT						
Model Selection	Part No.	Hitch	Front/Rear Shielding	Description	Shipping Wt. (lbs.)	Suggested List Price
DSO10.50W	96457	Semi-Mounted	Chain	540 rpm PTO, Cat 5 input drive, cylinder and hose.	2725	\$ 13,876.00

SECTION 2: ACCESSORIES (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1042260	Front and Rear Chain Shielding Replacement Kit	165	\$ 601.00

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

12-foot, For Compact/Utility Tractors – BW12

FACTORY ASSEMBLED

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 35 – 75 hp
 High-strength 12-gauge deck
 Cat 4 CV PTO drive
 Cat 3 wing drives
 540 rpm CV drive only
 Swivel clevis hitch

Cut: 1.5 inches diameter
 160 hp splitter gearbox,
 75 hp spindle gearboxes
 6-year limited gearbox warranty
Not for commercial use



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**12' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes solid clevis tongue, wing and lift cylinders, hoses, stroke control kit.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	Color	Description	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW12W	1043600	Woods Burnt Orange	1-3/8" 540 RPM CV Drive, Single Row Chain Shielding, Single Spring on Center Deck Wheel Yoke	4	2171	\$ 14,368.00
BW12W	1043600JD	Green	1-3/8" 540 RPM CV Drive, Single Row Chain Shielding, Single Spring on Center Deck Wheel Yoke	4	2171	14,368.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017040	21" O.D. Solid Laminated Tire & Rim	70	\$ 317.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1038933	Category 1 (1" Dia. Pin) Hitch	10	\$ 91.00

Model BW12 is available in the tractor colors as listed above.

"MATCH YOUR TRACTOR" TERMS & CONDITIONS

1. Product availability in most cases will be 30 to 60 days and sometimes less.
2. "Match Your Tractor" BW12s are built to order, requiring lead times that may vary.
3. "Match Your Tractor" orders are non-cancellable. Units and their accessories may not be returned.
4. Changes to existing orders must have the Dealer Service Supervisor's approval.
5. Repair parts are only available in Woods orange and all chain shield brackets are black (including Woods orange units).
6. Woods reserves the right to limit quantities and to modify or cancel this offering at any time.

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

10.5-foot, Standard-Duty – BW10.50

FACTORY ASSEMBLED

FEATURES & SPECIFICATIONS:

- | | |
|-------------------------------------|--|
| Recommended tractor hp: 45 – 200 hp | Cut: 3 inches diameter |
| Sloped top, 10-gauge deck | 210 hp splitter gearbox,
200 hp spindle gearboxes |
| Cat 6 CV PTO drive | 6-year limited gearbox warranty
(includes seals) |
| Cat 4 wing drive | |
| Clevis hitch | |



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**10.5' Single Right Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW10.50W	1045753	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	3775	\$ 18,909.00
BW10.50QW	1045754	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	3774	18,909.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)			
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045841	Front Double Row Chain Shield Kit	83	\$ 382.00
1045842	Rear Double Row Chain Shield Kit	60	294.00
1017310	Dual Hub Kit (for center section) – Add 2 Additional Wheels Per Kit	30	290.00
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	182.00
1045853	Cable Winch Kit	72	553.00
1045808	BW LED Light Kit	7	373.00
1045817	Pintle Ring Tongue Kit	35	589.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

15-foot, Standard-Duty – BW15.50

FACTORY ASSEMBLED

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 45 – 200 hp
 Sloped top, 10-gauge deck
 Cat 6 CV PTO drive
 Cat 4 wing drives
 Clevis hitch

Cut: 3 inches diameter
 210 hp splitter gearbox,
 200 hp spindle gearboxes
 6-year limited gearbox warranty
 (includes seals)



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**15' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW15.50W	1045750	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4270	\$ 19,046.00
BW15.50QW	1045751	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4169	19,046.00
BW15.50QW	1045752	1-3/4" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4169	19,210.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.	
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00	
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00	
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00	
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00	
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00	
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00	

SECTION 3: OPTIONS (Dealer-Installed)				
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price	
1045839	Front Double Row Chain Shield Kit	129	\$ 528.00	
1045840	Rear Double Row Chain Shield Kit	81	356.00	
1017310	Dual Hub Kit (1 kit for center; 1 kit for wings) – Add 2 Additional Wheels Per Kit	30	290.00	
1045853	Cable Winch Kit	72	553.00	
1045808	BW LED Light Kit	7	373.00	
1003696	T-Hose Kit	3	76.00	
1045817	Pintle Ring Tongue Kit	35	589.00	
1046047	Category 4 Clevis	20	199.00	

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

10.5-foot, Heavy-Duty – BW10.60

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

- Recommended tractor hp: 55 – 275 hp
- Sloped top, 7-gauge deck
- Cat 6 CV PTO drive
- Cat 4 wing drive
- Swivel clevis hitch
- Cut: 4 inches diameter
- 275 hp splitter gearbox, 225 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**10.5' Single-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW10.60W	1045768	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	4294	\$ 21,048.00
	1045769			Spring-Loaded @ Each Axle Arm	3	4403	22,343.00
BW10.60QW	1045770	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	4294	21,048.00
	1045771			Spring-Loaded @ Each Axle Arm	3	4403	22,343.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045841	Front Double Row Chain Shield Kit	83	\$ 382.00
1045842	Rear Double Row Chain Shield Kit	60	294.00
1017310	Dual Hub Kit (for center section) – Add 2 Additional Wheels Per Kit	30	290.00
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	182.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit and dual hub kit for center section; serial number 10007668087004 and older)	173	1,070.00
1046083	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit for wing section; serial number 10007668087004 and older)	87	499.00
614292	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit and dual hub kit for center section; serial number newer than 10007668087004)	173	997.00
614293	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit for wing section; serial number newer than 10007668087004)	87	499.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

10.5-foot, Heavy-Duty – BW10.60

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 55 – 275 hp
 Sloped top, 7-gauge deck
 Cat 6 CV PTO drive
 Cat 4 wing drive
 Swivel clevis hitch

Cut: 4 inches diameter
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**10.5' Single-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW10.60RW	1045774	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	4357	\$ 21,666.00
	1045775			Spring-Loaded @ Each Axle Arm	3	4466	22,962.00
BW10.60QRW	1045776	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	3	4357	21,666.00
	1045777			Spring-Loaded @ Each Axle Arm	3	4466	22,962.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045841	Front Double Row Chain Shield Kit	83	\$ 382.00
1045842	Rear Double Row Chain Shield Kit	60	294.00
1017310	Dual Hub Kit (for center section) – Add 2 Additional Wheels Per Kit	30	290.00
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	182.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit and dual hub kit for center section; serial number 10007668087004 and older)	173	1,070.00
1046083	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit for wing section; serial number 10007668087004 and older)	87	499.00
614292	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit and dual hub kit for center section; serial number newer than 10007668087004)	173	997.00
614293	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit for wing section; serial number newer than 10007668087004)	87	499.00
1046047	Category 4 Clevis	20	199.00

**Prices and specifications subject to change without notice.
 Prices effective January 1, 2021.** Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

15-foot, Heavy-Duty – BW15.60

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

- Recommended tractor hp: 55 – 275 hp
- Sloped top, 7-gauge deck
- Cat 6 CV PTO drive
- Cat 4 wing drives
- Swivel clevis hitch
- Cut: 4 inches diameter
- 275 hp splitter gearbox,
225 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**15' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW15.60W	1045756	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4454	\$ 23,203.00
	1045757			Spring-Loaded @ Each Axle Arm	4	4609	24,534.00
BW15.60QW	1045758	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4454	23,203.00
	1045759			Spring-Loaded @ Each Axle Arm	4	4609	24,534.00
BW15.60QW	1045760	1-3/4" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4454	23,366.00
	1045761			Spring-Loaded @ Each Axle Arm	4	4609	24,698.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045839	Front Double Row Chain Shield Kit	129	\$ 528.00
1045840	Rear Double Row Chain Shield Kit	81	356.00
1017310	Dual Hub Kit (1 kit for center; 1 kit for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for center & wing section; serial number 10007668087004 and older)	173	1,070.00
614292	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for center & wing section; serial number newer than 10007668087004)	173	997.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

15-foot, Heavy-Duty – BW15.60

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 55 – 275 hp
 Sloped top, 7-gauge deck
 Cat 6 CV PTO drive
 Cat 4 wing drives
 Swivel clevis hitch

Cut: 4 inches diameter
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**15' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)								
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price	
BW15.60RW	1045762	1-3/8" 540 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4517	\$ 24,093.00	
	1045763			Spring-Loaded @ Each Axle Arm	4	4672	25,426.00	
BW15.60QRW	1045764	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring on Center Deck Wheel Yoke	4	4517	24,093.00	
	1045765			Spring-Loaded @ Each Axle Arm	4	4672	25,426.00	
BW15.60QRW	1045767	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	4	4672	25,590.00	

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.	
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00	
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00	
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00	
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00	
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00	
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00	

SECTION 3: OPTIONS (Dealer-Installed)				
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price	
1045839	Front Double Row Chain Shield Kit	129	\$ 528.00	
1045840	Rear Double Row Chain Shield Kit	81	356.00	
1017310	Dual Hub Kit (1 kit for center; 1 kit for wings) – Add 2 Additional Wheels Per Kit	30	290.00	
1045853	Cable Winch Kit	72	553.00	
1045821	Shredding Kit	113	1,215.00	
1045808	BW LED Light Kit	7	373.00	
1003696	T-Hose Kit	3	76.00	
1045817	Pintle Ring Tongue Kit	35	589.00	
1045819	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for center & wing section; serial number 10007668087004 and older)	173	1,070.00	
614292	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for center & wing section; serial number newer than 10007668087004)	173	997.00	
1046047	Category 4 Clevis	20	199.00	

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

10.5-foot, Extreme-Duty – BW10.70

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

- Recommended tractor hp: 65 – 300 hp
- Sloped top, 1/4-inch deck
- Cat 6 CV PTO drive; Cat 5 wing drive
- Floating linkage on wing lift cylinder
- 1/4-inch side frame with 13-inch depth
- Swivel clevis hitch
- Hinge pin: 1 inch full length
- Cutting height: 2 – 15 inches;
Cutting width: 126 inches
- Cut: 4.5 inches diameter
- Transport width: 93 inches
(laminated wheels)
- 275 hp splitter gearbox,
225 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**10.5' Single-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW10.70W	1045792	1-3/8" 540 RPM CV Drive	Single Row	Single Spring Suspension	5	4665	\$ 22,522.00
	1045793			Spring-Loaded @ Each Axle Arm	5	4774	23,761.00
BW10.70QW	1045794	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring Suspension	5	4665	22,522.00
	1045795			Spring-Loaded @ Each Axle Arm	5	4774	23,761.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045841	Front Double Row Chain Shield Kit	83	\$ 382.00
1045842	Rear Double Row Chain Shield Kit	60	294.00
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	182.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit; serial number 10007668087004 and older)	173	1,070.00
1046083	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit; serial number 10007668087004 and older)	87	499.00
614292	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit; serial number newer than 10007668087004)	173	997.00
614293	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit; serial number newer than 10007668087004)	87	499.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

10.5-foot, Extreme-Duty – BW10.70

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 65 – 300 hp
 Sloped top, 1/4-inch deck
 Cat 6 CV PTO drive; Cat 5 wing drive
 Floating linkage on wing lift cylinder
 1/4-inch side frame with 13-inch depth
 Swivel clevis hitch
 Hinge pin: 1 inch full length

Cutting height: 2 – 15 inches;
 Cutting width: 126 inches
 Cut: 4.5 inches diameter
 Transport width: 93 inches
 (laminated wheels)
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**10.5' Single-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW10.70RW	1045798	1-3/8" 540 RPM CV Drive	Single Row	Single Spring Suspension	5	4728	\$ 23,090.00
	1045799			Spring-Loaded @ Each Axle Arm	5	4837	24,331.00
BW10.70QRW	1045801	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	5	4837	24,331.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.	
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00	
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00	
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00	
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00	
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00	
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00	

SECTION 3: OPTIONS (Dealer-Installed)				
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price	
1045841	Front Double Row Chain Shield Kit	83	\$ 382.00	
1045842	Rear Double Row Chain Shield Kit	60	294.00	
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	182.00	
1045853	Cable Winch Kit	72	553.00	
1045821	Shredding Kit	113	1,215.00	
1045808	BW LED Light Kit	7	373.00	
1045817	Pintle Ring Tongue Kit	35	589.00	
1045819	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit; serial number 10007668087004 and older)	173	1,070.00	
1046083	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit; serial number 10007668087004 and older)	87	499.00	
614292	Walking Tandem Kit (for center section, must be ordered with spring-loaded base unit; serial number newer than 10007668087004)	173	997.00	
614293	Walking Tandem Kit (for wing section, must be ordered with spring-loaded base unit and dual hub kit; serial number newer than 10007668087004)	87	499.00	
1046047	Category 4 Clevis	20	199.00	

**Prices and specifications subject to change without notice.
 Prices effective January 1, 2021.** Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

15-foot, Extreme-Duty – BW15.70

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 65 – 300 hp
 Sloped top, 1/4-inch deck
 Cat 6 CV PTO drive; Cat 5 wing drives
 Floating linkage on wing lift cylinders
 1/4-inch side frame with 13-inch depth
 Swivel clevis hitch
 Wing hinge pin: 1 inch full length

Cutting height: 2 – 15 inches;
 Cutting width: 180 inches
 Cut: 4.5 inches diameter
 Transport width: 96 inches
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**15' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW15.70W	1045780	1-3/8" 540 RPM CV Drive	Single Row	Single Spring Suspension	6	4840	\$ 26,019.00
	1045781	1-3/8" 540 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	4995	27,490.00
BW15.70QW	1045782	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring Suspension	6	4840	26,019.00
	1045783	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	4995	27,490.00
BW15.70QW	1045784	1-3/4" 1000 RPM CV Drive	Single Row	Single Spring Suspension	6	4840	26,179.00
	1045785	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	4995	27,652.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045839	Front Double Row Chain Shield Kit	129	\$ 528.00
1045840	Rear Double Row Chain Shield Kit	81	356.00
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for wing section only; serial number 10007668087004 and older)	173	1,070.00
614292	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for wing section only; serial number newer than 10007668087004)	173	997.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

15-foot, Extreme-Duty – BW15.70

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 65 – 300 hp
Sloped top, 1/4-inch deck
Cat 6 CV PTO drive; Cat 5 wing drives
Floating linkage on wing lift cylinders
1/4-inch side frame with 13-inch depth
Swivel clevis hitch
Wing hinge pin: 1 inch full length

Cutting height: 2 – 15 inches;
Cutting width: 180 inches
Cut: 4.5 inches diameter
Transport width: 96 inches
275 hp splitter gearbox,
225 hp spindle gearboxes
6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**15' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)

Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW15.70RW	1045786	1-3/8" 540 RPM CV Drive	Single Row	Single Spring Suspension	6	4903	\$ 27,458.00
	1045787			Spring-Loaded @ Each Axle Arm	6	5059	28,929.00
BW15.70QRW	1045788	1-3/8" 1000 RPM CV Drive	Single Row	Single Spring Suspension	6	4903	27,458.00
	1045789			Spring-Loaded @ Each Axle Arm	6	5059	28,929.00
BW15.70QRW	1045791	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	5059	29,091.00

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)

Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)

Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1045839	Front Double Row Chain Shield Kit	129	\$ 528.00
1045840	Rear Double Row Chain Shield Kit	81	356.00
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1045853	Cable Winch Kit	72	553.00
1045821	Shredding Kit	113	1,215.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1045817	Pintle Ring Tongue Kit	35	589.00
1045819	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for wing section only; serial number 10007668087004 and older)	173	1,070.00
614292	Walking Tandem Kit (1 kit for center section; 1 kit for wings, must be ordered with spring-loaded base unit and dual hub kit for wing section only; serial number newer than 10007668087004)	173	997.00
1046047	Category 4 Clevis	20	199.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

20-foot, Standard-Duty – BW20.51

FACTORY ASSEMBLED

FEATURES & SPECIFICATIONS:

- | | |
|-------------------------------------|--|
| Recommended tractor hp: 70 – 200 hp | Fully baffled decks |
| Sloped top, 10-gauge deck | Cut: 2 inches diameter |
| Cat 6 CV PTO drive | 250 hp splitter gearbox,
200 hp spindle gearboxes |
| Cat 4 wing drives | 6-year limited gearbox warranty |
| Clevis hitch | |



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**20' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW20.51W	614120	1-3/8" 540 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6050	\$ 28,014.00
BW20.51QW	614122	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6046	28,014.00
BW20.51QW	614248	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6046	28,160.00

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)			
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1044331WW	Double Row Chain Shield Kit, Front and Rear	TBD	\$ 1,822.00
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1019456	Cable Winch Kit	58	451.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1031395	Pintle Ring Kit	34	541.00
614347	Spring-Loaded Wing Lock-Ups (<3m transport width)	107	636.00
603864	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with dual hub kit for center and wing section)	180	1,162.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

20-foot, Heavy-Duty – BW20.61

FACTORY ASSEMBLED

FEATURES & SPECIFICATIONS:

- | | |
|-------------------------------------|--|
| Recommended tractor hp: 70 – 300 hp | Fully baffled decks |
| Sloped top, 10-gauge deck | Cut: 3 inches diameter |
| Cat 6 CV PTO drive | 275 hp splitter gearbox,
225 hp spindle gearboxes |
| Cat 4 wing drives | 6-year limited gearbox warranty |
| Swivel clevis hitch | |



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**20' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW20.61W	614250	1-3/8" 540 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6406	\$ 31,928.00
BW20.61W	614251	1-3/8" 540 RPM CV Drive	Double Row	Spring-Loaded @ Each Axle Arm	6	6660	32,307.00
BW20.61QW	614252	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6543	31,928.00
BW20.61QW	614253	1-3/8" 1000 RPM CV Drive	Double Row	Spring-Loaded @ Each Axle Arm	6	6777	32,307.00
BW20.61QW	614255	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	6543	32,084.00

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)			
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1044331WW	Double Row Chain Shield Kit, Front and Rear	TBD	\$ 1,822.00
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1019456	Cable Winch Kit	58	451.00
614356	Stalk Shredding Kit	125	1,253.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1019451	Pintle Ring Kit	33	579.00
614347	Spring-Loaded Wing Lock-Ups (<3m transport width)	107	636.00
603864	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with dual hub kit for center and wing section)	180	1,162.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

13.5-foot, Extreme-Duty – BW13.71

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

- Recommended tractor hp: 70 – 300 hp
- Sloped top, (2) 10-gauge deck
- Cat 6 CV PTO drive; Cat 5 wing drive
- Floating linkage on wing lift cylinder
- 1/4-inch side frame with 12.5-inch depth
- Swivel clevis hitch
- Fully baffled decks
- Hinge pin: 1 inch full length
- Cutting height: 2 – 15 inches;
- Cutting width: 162 inches
- Cut: 4 inches diameter
- Transport width: 106 inches
- 275 hp splitter gearbox, 225 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**13.5' Single Right Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW13.71W	614271	1-3/8" 540 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	5	7860	\$ 26,609.00
BW13.71QW	614273	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	5	7860	26,609.00

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)			
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	\$ 182.00
1019456	Cable Winch Kit	58	451.00
1045808	BW LED Light Kit	7	373.00
1019451	Pintle Ring Kit	33	579.00
603864	Walking Tandem Kit (for center section)	180	1,162.00
603865	Walking Tandem Kit (for wing section, must be ordered with dual hub kit)	90	590.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® SINGLE-WING ROTARY CUTTER

13.5-foot, Extreme-Duty – BW13.71

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 70 – 300 hp
 Sloped top, (2) 10-gauge deck
 Cat 6 CV PTO drive; Cat 5 wing drive
 Floating linkage on wing lift cylinder
 1/4-inch side frame with 12.5-inch depth
 Swivel clevis hitch
 Fully baffled decks
 Hinge pin: 1 inch full length

Cutting height: 2 – 15 inches;
 Cutting width: 162 inches
 Cut: 4 inches diameter
 Transport width: 106 inches
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**13.5' Single Right Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT								
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price	
BW13.71QREVRW w/Reverse Rotation	614288	1-3/8" 1000 RPM CV Drive	Double Row	Spring-Loaded @ Each Axle Arm	5	8053	\$ 28,265.00	

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.	
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00	
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00	
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00	
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00	
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00	
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00	

SECTION 3: OPTIONS (Dealer-Installed)				
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price	
1028801	Dual Hub Kit (for wing section) – Add 1 Additional Wheel Per Kit	16	\$ 182.00	
1019456	Cable Winch Kit	58	451.00	
1045808	BW LED Light Kit	7	373.00	
1019451	Pintle Ring Kit	33	579.00	
603864	Walking Tandem Kit (for center section)	180	1,162.00	
603865	Walking Tandem Kit (for wing section, must be ordered with dual hub kit)	90	590.00	

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

20-foot, Extreme-Duty – BW20.71

FACTORY ASSEMBLED: NO DECK RINGS

FEATURES & SPECIFICATIONS:

- Recommended tractor hp: 70 – 300 hp
- Sloped top, (2) 10-gauge deck
- Cat 6 CV PTO drive; Cat 5 wing drives
- Floating linkage on wing lift cylinders
- 1/4-inch side frame with 12.5-inch depth
- Swivel clevis hitch
- Fully baffled decks
- Wing hinge pin: 1 inch full length
- Cutting height: 2 – 15 inches;
- Cutting width: 240 inches
- Cut: 4 inches diameter
- Transport width: 120 inches
- 275 hp splitter gearbox,
- 225 hp spindle gearboxes
- 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**20' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit.
MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW20.71QW	614259	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	7309	\$ 34,834.00
BW20.71QW	614261	1-3/4" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	7309	34,965.00

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)			
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00

SECTION 3: OPTIONS (Dealer-Installed)			
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price
1044331WW	Double Row Chain Shield Kit, Front and Rear	TBD	\$ 1,822.00
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00
1019456	Cable Winch Kit	58	451.00
614356	Stalk Shredding Kit	125	1,253.00
1045808	BW LED Light Kit	7	373.00
1003696	T-Hose Kit	3	76.00
1019451	Pintle Ring Kit	33	579.00
614347	Spring-Loaded Wing Lock-Ups (<3m transport width)	107	636.00
603864	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with dual hub kit for center and wing section)	180	1,162.00

Prices and specifications subject to change without notice.
Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

BATWING® DUAL-WING ROTARY CUTTER

20-foot, Extreme-Duty – BW20.71

FACTORY ASSEMBLED: WITH DECK RINGS

FEATURES & SPECIFICATIONS:

Recommended tractor hp: 70 – 300 hp
 Sloped top, (2) 10-gauge deck
 Cat 6 CV PTO drive; Cat 5 wing drives
 Floating linkage on wing lift cylinders
 1/4-inch side frame with 12.5-inch depth
 Swivel clevis hitch
 Fully baffled decks
 Wing hinge pin: 1 inch full length

Cutting height: 2 – 15 inches;
 Cutting width: 240 inches
 Cut: 4 inches diameter
 Transport width: 120 inches
 275 hp splitter gearbox,
 225 hp spindle gearboxes
 6-year limited gearbox warranty



WARNING: CHAIN SAFETY SHIELDING STANDARD EQUIPMENT. Chain safety shielding must be used for all non-agricultural uses and in areas where the possibility of thrown objects could be hazardous to persons or property. The maximum transport speed for towed and semi-mounted machines is 20 mph (32 KM/H). Regardless of the maximum speed capability of the towing tractor, do not exceed the implement's maximum transport speed.

**20' Dual-Wing Batwing Cutter, Factory-Assembled (less wing wheels).
 Base Unit includes swivel clevis tongue, wing and lift cylinders, hoses, stroke control kit, deck rings.
 MUST CHOOSE FROM SECTIONS 1 & 2 FOR A COMPLETE MACHINE.**

SECTION 1: BASE UNIT (MUST Choose One)							
Model Selection	Part No.	PTO	Chain Shielding	Wheel Yoke Suspension	Tires Req'd	Shipping Wt. (lbs.)	Suggested List Price
BW20.71RW	614264	1-3/8" 540 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	7468	\$ 36,066.00
BW20.71QRW	614266	1-3/8" 1000 RPM CV Drive	Single Row	Spring-Loaded @ Each Axle Arm	6	7468	36,066.00

NOTE: 1000 rpm recommended for tractors over 100 HP.

SECTION 2: WHEELS AND TIRES (Dealer-Installed – MUST Choose Part No. & Quantity)				
Part No.	Description	Shipping Wt. Ea. (lbs.)	Suggested List Price Ea.	
1017088	15" Wheel Rims for Pneumatic Tires (dealer supplies tires)	18	\$ 72.00	
1017040	21" O.D. Solid Laminated Tire & Rim	70	317.00	
1017030	29 x 9 x 15 Used Aircraft Tire & Rim	75	344.00	
1017030F	29" O.D. Foam-Filled Used Aircraft Tire w/Wheel	156	466.00	
1039976	Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	56	367.00	
1039976F	Foam-Filled Severe-Duty Ag 20PR Tire & Rim, 25.5 x 8-14, 5-Bolt	108	426.00	

SECTION 3: OPTIONS (Dealer-Installed)				
Part No.	Description	Shipping Wt. (lbs.)	Suggested List Price	
1044331WW	Double Row Chain Shield Kit, Front and Rear	TBD	\$ 1,822.00	
1017310	Dual Hub Kit (for wings) – Add 2 Additional Wheels Per Kit	30	290.00	
1019456	Cable Winch Kit	58	451.00	
614356	Stalk Shredding Kit	125	1,253.00	
1045808	BW LED Light Kit	7	373.00	
1003696	T-Hose Kit	3	76.00	
1019451	Pintle Ring Kit	33	579.00	
614347	Spring-Loaded Wing Lock-Ups (<3m transport width)	107	636.00	
603864	Walking Tandem Kit (1 kit for center; 1 kit for wings, must be ordered with dual hub kit for center and wing section)	180	1,162.00	

Prices and specifications subject to change without notice.
 Prices effective January 1, 2021. Supersedes all previous pricing.
 Woods reserves the right to limit quantities and apply surcharges at any time.

